

# AUGERS





### **SRA**

SRA STYLE AUGERS FOR DRILLING IN THE TOUGHEST CONDITIONS, SOLID ROCK, CONCRETE, FRACTURED ROCK, FROZEN GROUND AND COMPACTED SOILS.

FEATURES: AVAILABLE IN 48" LENGTH FOR HYDRAULIC DRIVES AND 36" FOR TM-48  
4.5" TO 7" DIAMETERS  
HEAVY DUTY 3/4" THICK BORING HEAD  
CARBIDE BULLET STYLE TEETH  
3/8" THICK FLIGHTING



### **RAD**

RAD STYLE AUGERS FOR DRILLING IN THE TOUGHEST CONDITIONS, SOLID ROCK, CONCRETE, FRACTURED ROCK, FROZEN GROUND AND COMPACTED SOILS.

FEATURES: AVAILABLE IN 48" LENGTH FOR HYDRAULIC DRIVES AND 36" FOR TM-48  
8" TO 36" DIAMETERS  
HEAVY DUTY 3/4" THICK BORING HEAD  
CARBIDE BULLET STYLE TEETH  
3/8" THICK FLIGHTING



### **RSA**

RSA STYLE AUGERS FOR DRILLING IN DIFFICULT GROUND CONDITIONS, COMPACTED SOILS, HEAVY CLAY, ASPHALT, FROZEN GROUND, AND FRACTURED ROCK.

FEATURES: AVAILABLE IN 48" LENGTH FOR HYDRAULIC DRIVES AND 36" FOR TM-48  
6" TO 36" DIAMETERS  
CAST BORING HEAD  
HARDENED DRIVE IN TEETH  
HARDENED FISHTAIL PILOT  
DOUBLE FLIGHT



### **SDA**

SDA STYLE AUGERS FOR STANDARD TO MODERATE DRILLING CONDITIONS, DIRT CLAY AND SMALL FRACTURED ROCK.

FEATURES: AVAILABLE IN 48" AND 54" OVER ALL LENGTHS  
4.5" TO 36" DIAMETERS  
CAST BORING HEAD  
HARDENED DRIVE IN TEETH  
HARDENED FISHTAIL PILOT  
SINGLE FLIGHT



### **PUFF**

PUFF STYLE AUGERS FOR DRILLING T-POST HOLES IN DIRT, CLAY, COMPACTED SOILS, FROZEN GROUND, FRACTURED ROCK, SOLID ROCK AND CONCRETE.

FEATURES: REPLACEABLE 2" CARBIDE CUTTING HEAD



P.O. Box 270 · Belton, Texas 76513  
1-800-242-9410 · Fax 254-939-9408  
www.belltec.net · sales@belltec.net