

BELLTEC H-SERIES AUGER DRIVES

5 Year Warranty



Belltec H-Series Auger Drives

The Belltec H-Series hydraulic auger drives are available in three models for systems operating between 10 and 35 GPM and 2000 to 3000 PSI. The H-Series planetary outperforms and has heavier components than any of its competitors. First tubular frame on the market with the largest and strongest cradle. Mounting frame mounts to all modern skid loaders with the universal attach system. The H Series units are ideal for the toughest drilling applications from dirt to solid rock and concrete when paired with the correct H Series auger.

No Case Drain Hoses Required

Features:

- Heaviest in Class Planetary Gearbox with No Snaps Rings
- Heavy Duty Hexagon Housing
- Heavy Duty Nut Prevents Shaft Pull Out
- 2" Hex Output Shaft
- Heavy Duty Motors with High Pressure Seal

MODEL H-200

ORDER NUMBER 113001

MAXIMUM OUTPUT TORQUE	2000 FT-LBS
RECOMMENDED FLUID FLOW	10-20 GPM
MAXIMUM PRESSURE-CONTINUOUS	3000 PSI
RECOMMENDED MAX AUGER DIA-ROCK	24 INCHES
RECOMMENDED MAX AUGER DIA-DIRT.....	30 INCHES

OUTPUT SPEED

FLOW GPM	SPEED RPM
10	48
12	55
14	64
16	73
18	82
20	92

OUTPUT TORQUE

PRESSURE PSI	TORQUE Lb-Ft
2000	1339
2200	1480
2400	1607
2600	1740
2800	1874
3000	2008



Exclusive bolt on 2" hex output shaft significantly reduces costly down time and repair costs if a shaft is bent or broken.

MODEL H-300

ORDER NUMBER 113014

MAXIMUM OUTPUT TORQUE	3000 FT-LBS
RECOMMENDED FLUID FLOW	15-30 GPM
MAXIMUM PRESSURE-CONTINUOUS	3000 PSI
RECOMMENDED MAX AUGER DIA-ROCK	36 INCHES
RECOMMENDED MAX AUGER DIA-DIRT	36 INCHES

OUTPUT SPEED

FLOW GPM	SPEED RPM
15	47
18	56
22	68
26	81
28	87
30	93

OUTPUT TORQUE

PRESSURE PSI	TORQUE Lb-Ft
2000	1958
2200	2066
2400	2350
2600	2546
2800	2742
3000	2937



Extra large step with non-skid for entering and exiting skid loaders and owners manual canister so the manual stays with the unit at all times.

MODEL H-350

ORDER NUMBER 113016

MAXIMUM OUTPUT TORQUE	3000 FT-LBS
RECOMMENDED FLUID FLOW	15-30 GPM
MAXIMUM PRESSURE-CONTINUOUS	3000 PSI
RECOMMENDED MAX AUGER DIA-ROCK	36 INCHES
RECOMMENDED MAX AUGER DIA-DIRT	36 INCHES

OUTPUT SPEED

FLOW GPM	SPEED RPM
20	51
24	62
26	67
28	72
30	77
35	90

OUTPUT TORQUE

PRESSURE PSI	TORQUE Lb-Ft
2000	2388
2200	2985
2400	3582



Large cradle holds drive in place and allows for better visibility while in transport position.



P.O. Box 270 · Belton, Texas 76513
 1-800-242-9410 · Fax 254-939-9408
 www.belltec.net · sales@belltec.net